



MAX-GPRO8 8-Channel DVR



- Remote monitor with IE Browser, iPhone, Windows Mobile ●
- Real Time Recording with H264 video compression codec ●
- 8 video channels ●
- Infrared remote control ●
- USB Mouse ●

Features

- Mobile Surveillance** - 3G and 3.5G compatible. Use iPhone, Windows Mobile, or Nokia devices.
- Pentaplex Operation** - Do multiple tasks like record, playback, watch live video, perform a backup or network operation, etc., at the same time.
- Remote Surveillance** - Use mobile surveillance tools, or Internet Explorer browser and client software. Functions include monitoring, playback, recording, and DVR control.
- Multiple Recording Modes** - Timer, motion triggered, and alarm triggered.
- Easy Network Connection** - RJ45-style connector on back panel supports multiple protocols TCP/IP, DHCP, DDNS, and PPPoE.
- Audio Support** - 1 (one) audio channel in, 1 (one) audio channel out (mono).
- PTZ Support** - Multiple protocols supported, RS485 interface
- Search Modes** - Search recorded video using a variety of search criteria.
- Miscellaneous** - Pan/tilt/zoom support, RS485, USB mouse support, multilingual on-screen display (OSD) menu, multiple display and record modes.




Storage & Hardware Specifications

HDD interface: up to two SATA HDDs
External storage: portable DVR burner or HDD (USB 2.0) optional
Network Interface: RJ45 10M/100M Ethernet Auto Detect
Network protocols: TCP/IP, PPPOE, DHCP, DDNS, EMAIL
Compression: Standard H.264 (H264)
Video format: NTSC/PAL
Video input: 8 channels (BNC connectors)
Video output: 1 composite, 1 VGA
Video backup: AVI, MPEG4, H.264 RAW
Audio input: 1 channel
Audio output: 1 (mono)
Audio compression: G.726 8Kx16bit ADPCM Mono
Pan/Tilt/Zoom Support: RS485 communication with Pelco D/P, Samsung, Panasonic protocols
Power: 12VDC (included), 30W - 230W (depending on HDDs)
Operating Temperature: 10°~40°C (50°~104°F)

Video & System Specifications

Maximum Recording Rate: Real Time 240 images per second (IPS)	
Display Frame Rate: Real Time 240 images per second (IPS)	
Record Resolution	Playback Resolution
NTSC CIF 240 IPS (352 x 240) 2CIF 120 IPS (704 x 240) D1 60 IPS (704 x 480)	NTSC CIF 120 IPS (352 x 240) 2CIF 60 IPS (704 x 240) D1 30 IPS (704 x 480)
Cameras On-Screen: View 1 camera or split screen to 4 or 9 equal sectors (9th sector blank) to view multiple channels with audio	
Playback: View 1 camera or split screen to 4 or 9 equal sectors (9th sector blank) to view multiple channels with audio	
Video Backup Portability: View video files in MPEG4 or AVI format on any PC	
USB 2.0 Interface for optional portable HDD / Flash Drive / DVD Burner and for Firmware Upgrade (when available)	
Remote Operation: View or Operate using client software, IE browser (Windows 2000, XP, Vista, & Ver. 7 compatible)	
Recording Modes: Power-On Auto Record / Manual / Schedule / Motion / Sensor	
Operation Modes: Simplex/Triplex selectable - simultaneous monitor, record, playback single channel/quad	
Video Search Functions: Time, alarm event, motion detection event, list	
Mobile Surveillance (3G and 3.5G): iPhone, Windows Mobile, Nokia, Symbian compatible	
Users Manual, Infrared Remote Control and USB Mouse Included	



USB MOUSE INCLUDED!



IR REMOTE CONTROL INCLUDED!