

# 16 Channel MPEG4 DVR System



**MPEG-4**

**NETWORK**



### Integrated Internal Back Up (UPS)\*

Provides a stable stream of power during blackouts, momentary power interruptions & variable voltage incidents for up to **2** hours.  
(part# NUB8UP)



Software Screenshot with Clickable Calendar



Independent Channel Adjustment

### Independent CH Adjustment & Control

- Full Graphical Menu
- Easy Calendar Search
- Wireless IR Remote Control
- New Client Software
- Multi Channel Playback

Compression	MPEG4
Display Speed	Real Time for all Channels
Recording Speed	120 Images Per Second
Display Resolution	720 x 480 (D1)
Recording Resolution	360 x 240 (CIF), 720 x 240 (Half D1), 720 x 480 (D1)
Video Inputs	16 CH (Looping Outputs)
Video Output	1 BNC Composite Video / VGA / S-VIDEO / SPOT Monitor
Audio	4 Inputs / 1 Output
Alarm	16 Inputs / 4 Outputs
PTZ Controls	RS485 Output on Board
Controls	IR Remote Control, USB Plug & Play Mouse
Adjustable Video	Brightness, contrast, color, hue, sharpness
Search Mode	Easy Calendar search, Smart Motion search, Advanced search with preview
Motion Detection	Adjustable motion grid
Storage	3 Internal HDD (Mirroring Raid 1)
Multiplexer Function	(Triplex) Remote view, playback, recording, back-up
Menu	Full Interactive GUI (Graphic User Interface)
Back-up	CD/RW and USB output standard
Network	TCP/IP (Remote Access with Client software and IE)
Operation Temperature	41°F~104°F (5°C~40°C)
Power	12 VDC External Transformer (100~240VAC)
Dimensions	432(w) x 406(d) x 89(h) mm

\* Optional Feature Sold Separately